

Smart Fieldmeter® Digital, Model: RFP-05M



Smart Fieldmeter® Digital:

Electromagnetic field monitor having **flexible and expandable architecture, state of the art design with convenience and simplicity** for users on a budget.

Smart Fieldmeter® Digital (SFD) Features:

- SFD can operate with **multiple probes**, both current and future models. Calibration factors for multiple probes are stored internally and can be updated from SD card by the user.
- Extremely large SFD dynamic range with **auto-ranging** function offers high accuracy and simple operation without any additional switching.
- Advanced programmable data sampling with **time averaging and spatial averaging** allows monitoring and recording of time variable signals to comply with various RF safety and regulatory standards.
- **Internal data logging with removable memory card** provides programmable and practically unlimited data storage. No PC is needed for data recording - log the data and read it later.
- Unique **auto-zero** function can be operated either automatically or manually even in the presence of the strongest RF fields, thus ensuring the high sensitivity and long term stability.

- **Serial bidirectional data port** is compatible with IM (Insulated Modem) line of accessories, allowing the isolated USB charging and PC data exchange and/or fiber optic PC data transfer - fully eliminating any wires connected to the meter.
- **IR remote control** allows SFD control and operation from a distance - no hands, no wires (Optional).
- **Sound alarm** with variable threshold warns if the preset level is exceeded.
- **Portable lightweight design** with detachable isotropic probe and standard battery (**two AA primary or rechargeable cells**) offers flexibility and advantages in the field.

- SFD can display the data both in **field strength and power density units**.
- Bright **color OLED display** can be set to display only the information important to the user. Maximized display mode ensures **good visibility from a distance**.
- **Graphical display feature** allows showing the real time data plots on screen.
- **User friendly interface** puts all frequently done functions at the upper screens making them easy to find and to use.



Smart Fieldmeter® Digital, Model: RFP-05M



System Parameters of SFD Meter RFP-05M with probes:

- Probe PI-01:** 0.2 MHz - 3 GHz.
0.2 - 600 V/m.
- Probe PI-01E:** 0.1 MHz - 6 GHz.
0.3 - 600 V/m.
- Probe PI-03:** 3 MHz - 18 GHz.
0.8 - 800 V/m.
- PI-03P (Pulsed):** 100 MHz-18 GHz,
70-1400 V/m.
- Probe PI-01V:** 800 -1900 MHz.
0.4 - 500 V/m.
- Probe PI-H1:** 0.5 MHz - 50 MHz.
0.05 - 20 A/m.

- Calibration Accuracy: +/-0.5 dB
- Linearity deviation: +/- 0.5 dB.
- Battery life: >20 hours.
- Warranty 1 year.
- **US NIST** (USA National Institute of Standards) / **UK NPL** (UK National Physical Laboratory) traceable certificate is supplied with every unit.



Purchasing the Smart Fieldmeter®

You may find more information about our products to buy the **Smart Fieldmeter®** from our web site: www.emctd.com.

To inquire about **Smart Fieldmeter®** send us e-mail exid@emctd.com, or give us a call: 508-292-1833.

We can arrange the demonstration of **Smart Fieldmeter®** by our distributor in your country.

Our mail address:
EMC Test Design, LLC® P.O. Box 600532,
Newton, MA 02460, USA.

